

LARGE TRIM SWITCHES, 4 & 5-WAY

T4/T5
4-WAY
TOGGLES

Ihr offizieller Vertriebspartner



ALDERS
Indicate. Control. Connect.

ALDERS electronic GmbH
Arnoldstraße 19
47906 Kempen
+49 2152 8955-0
vertrieb@alders.de / www.alders.de

4-WAY TOGGLE SWITCHES WITH OR WITHOUT CENTER PUSHBUTTON

T4-0010

Actuation: Center position maintained, all other positions momentary
Rating: 5 amps Resistive @ 30VDC sea level
3 amps Inductive @ 30VDC sea level
DWV: 1050Vrms @ sea level
400Vrms @ 70,000 feet
Electrical Life: 100,000 cycles
Enclosure: Dusttight per MIL-PRF-8805 Design 2
Button: Black thermoplastic
Case: Black anodized aluminum alloy



T5-0004

Actuation: Toggle & Pushbutton: center position maintained, all other positions momentary
Rating: 2 amps Resistive @ 28VDC or 115VAC/60Hz
DWV: 1050Vrms
Electrical Life: 50,000 cycles
Enclosure: Dusttight per MIL-PRF-8805 Design 2
Button: Black nylon
Case: Black anodized aluminum alloy



T4-0065

Actuation: Center position maintained, all other positions momentary
Rating: 5 amps Resistive @ 30VDC sea level
2.5 amps Resistive @ 70,000 feet
3 amps Inductive @ 30VDC sea level
1.5 amps Inductive @ 70,000 feet
DWV: 1050Vrms @ sea level
400Vrms @ 70,000 feet
Electrical Life: 100,000 cycles
Enclosure: Dusttight per MIL-PRF-8805 Design 2
Button: Black nylon
Case: Black anodized aluminum alloy



T5-0015

Actuation: Toggle & Pushbutton: center position maintained, all other positions momentary
Rating: 2 amps Resistive @ 28VDC or 115VAC/60Hz
DWV: 1050Vrms
Electrical Life: 50,000 cycles
Enclosure: Dusttight per MIL-PRF-8805 Design 2
Button: Gray thermoplastic



T4-0082

Actuation: Toggle: center position maintained, all other positions momentary
Rating: 5 amps Resistive @ 30VDC sea level
3 amps Inductive @ 30VDC sea level
DWV: 1050Vrms @ sea level
Electrical Life: 50,000 cycles
Enclosure: Resilient per MIL-PRF-8805 Design 4
Button: Black nylon
Case: Aluminum alloy



T5-0018

Actuation: Toggle & Pushbutton: center position maintained, all other positions momentary
Rating: 2 amps Resistive @ 28VDC or 115VAC/60Hz
DWV: 1050Vrms
Electrical Life: 50,000 cycles
Enclosure: Dusttight per MIL-PRF-8805 Design 2
Button: Black thermoplastic
Case: Black anodized aluminum alloy



T4-0111

Actuation: Toggle: center position maintained, all other positions momentary
Rating: 2 amps Resistive @ 28 VDC sea level
.5 amps Inductive @ 28 VDC sea level
DWV: 1050Vrms @ sea level
Electrical Life: 100,000 cycles, each direction
Enclosure: Dusttight per MIL-PRF-8805 Design 2
Button: Black Nylon
Case: Black anodized aluminum alloy



T5-0028

Actuation: Toggle & Pushbutton: center position maintained, all other positions momentary
Rating: 2 amps Resistive @ 28VDC or 115VAC/60Hz
DWV: 1050Vrms
Electrical Life: 50,000 cycles
Enclosure: Dusttight per MIL-PRF-8805 Design 2
Button: Black thermoplastic
Case: Black anodized aluminum alloy



NOTE: Contact factory for additional configurations.

Specifications Subject To Change Without Notice

www.ottoexcellence.com 235

TRIM SWITCHES