# PUSHBUTTONS PER MIL-PRF-8805/96

### MOMENTARY ACTION NORMALLY OPEN OR NORMALLY CLOSED



## **Features:**

- MIL-PRF-8805/96 qualified
- Momentary snap-action
- Sealed or unsealed
- Compact, space-saving design
- Black or red button colors available
- Clear or black case colors available
- RoHS compliant


### Momentary, Normally Open


	-	-	-	
OTTO PART NUMBER	MILITARY PART NUMBER	SEAL	CASE COLOR	BUTTON COLOR
PE-1111	M8805/96-00I	UNSEALED	CLEAR	RED
PE-1112	M8805/96-002	UNSEALED	CLEAR	BLACK
PE-1121	M8805/96-005	UNSEALED	BLACK	RED
PE-1122	M8805/96-006	UNSEALED	BLACK	BLACK
PE - 1211	M8805/96-009	DUST TIGHT	CLEAR	RED
PE - 1212	M8805/96-010	DUST TIGHT	CLEAR	BLACK
PE - I 22 I	M8805/96-013	DUST TIGHT	BLACK	RED
PE - I 222	M8805/96-014	DUST TIGHT	BLACK	BLACK

	-	-		
OTTO PART NUMBER	MILITARY PART NUMBER	SEAL	CASE COLOR	BUTTON COLOR
PE-2111	M8805/96-003	UNSEALED	CLEAR	RED
PE-2112	M8805/96-004	UNSEALED	CLEAR	BLACK
PE - 2121	M8805/96-007	UNSEALED	BLACK	RED
PE - 2122	M8805/96-008	UNSEALED	BLACK	BLACK
PE - 2211	M8805/96-011	DUST TIGHT	CLEAR	RED
PE - 2212	M8805/96-012	DUST TIGHT	CLEAR	BLACK
PE - 222 I	M8805/96-015	DUST TIGHT	BLACK	RED
PE - 2222	M8805/96-016	DUST TIGHT	BLACK	BLACY

Standard Characteristics/Ratings: ELECTRICAL RATINGS:				
Sea Level @ 28VDC or 115VAC, 60/400Hz				
5A				
2A				
1000Vrms				
25,000 cycles				
50,000 cycles				
Unsealed per MIL-PRF-8805 Design 1 or Dusttight per MIL-PRF-8805 Design 2				
: -55°C to +85°C				
1.5 lbs. +/- 0.5 lb. (unsealed) 1.75 lbs. +/- 0.5 lb. (dusttight)				
0.095 inches +/- 0.015 inches				
0.010 inches min				
0.010 inches min				
Anodized aluminum alloy, clear or black				
Thermoplastic				
Silver alloy				
Hex nut and lockwasher				

## PE-1 Series Shown





PE

MILITARY PUSHBUTTONS